



CODE COMPLIANCE AND FIRE PERFORMANCE

CERTIFICATION AND TESTING

- ICC-certified (ESR-1365) as a code-compliant component of fire-rated wall assemblies and roof deck applications
 - Class A and 30-Minute Flame Spread Rating (ASTM E84, UL723)
 - Meets 15-Minute Thermal Barrier requirements (UBC 26-2)
 - CALFIRE/OSFM code-approved (CBC Chapter 7A) for use in exterior walls, eaves and soffits in California WUI Zones
-

RELEVANT LISTINGS/ASSEMBLIES

- 2-hour Load-Bearing Fire-Rated Exterior Walls:
 - UL Listing BXUV.U349
 - UL Listing BXUV.W408
 - UL Listing BXUV.W408 Extended
 - UL Listing BXUV.V312
 - 1-hour Load-Bearing Fire-Rated Exterior Walls:
 - Intertek Listing LPB/WPPS-60-01
 - UL Listing BXUV.V311
 - 2-hour Load-Bearing Fire-Rated Interior Walls:
 - UL Listing BXUV.U350
 - Roof Decking Application to Satisfy Vertical Continuity Requirements for Fire Walls
-

WEATHER RESISTANCE

Exposure 1 Classification – Certified to withstand normal exposure to moisture during construction delays.