



DESIGNERS CHOOSE **LP® FLAMEBLOCK® FIRE-RATED SHEATHING OVER FLAMEDXX® FOR A REASON.**

When architects, engineers and specifiers choose LP® FlameBlock® Fire-Rated OSB Sheathing, they're selecting today's most innovative fire-resistant material for wall assemblies and roof decks. There is no equivalent to LP FlameBlock sheathing.

Here's how the two products match up in a head-to-head comparison:

LP® FlameBlock® Fire-Rated OSB Sheathing

FLAMEDXX® Fire Retardant Treated OSB

Exposure 1 classification; can withstand normal exposure to moisture during storage and construction without compromising its fire-resistant properties

Exposure to precipitation during storage or installation should be avoided

Certified for Type II, Type III and Type V construction

Certified for Type V construction

LP FlameBlock sheathing is a code-compliant component of nine different UL® listed wall assemblies

FLAMEDXX is not a listed component of any UL® listed wall assemblies

Uses patented non-combustible Pyrotite® (cementitious) layer applied to OSB

Uses Fire-retardant coating applied to OSB which should not be exposed to precipitation

WEATHERABILITY

CONSTRUCTION TYPES

UL® LISTED ASSEMBLIES

FIRE-RESISTANT TECHNOLOGY

FLAMEDXX sheathing shown below



Learn more about why architects and specifiers prefer LP FlameBlock sheathing, and why builders should hold the spec on every project.

Visit LPCorp.com/FlameBlock today!

LPCorp.com/FlameBlock

BUILD WITH US.®

