



Flooring or Plasterboard Attachment to LP® SolidStart™ LVL

LP® Building Products incorporates state-of-the-art technology when producing LP® SolidStart™ Laminated Veneer Lumber (LVL) for the construction industry. This proprietary six-sided orange SiteCote™ and/or wax edge seal is designed to provide superior water shedding characteristics and minimises swelling and cupping during the normal storage and construction build cycle.



Plasterboard and Flooring Attachment

LP SolidStart LVL makes a great wall stud and floor joist; straight, long and true. For walls use the



recommended screwing or nailing attachment for ceiling plasterboard (or high temperature wall or bracing areas). For floors use the recommended screwing (or nailing) attachment for flooring. Glue will not adequately stick to the LP SolidStart LVL studs and joists with SiteCote and/or wax edge seal.

Sub-Floor Bearers and Joists

LP SolidStart LVL sub-floor bearers and joists are available without wax seal on the edges to allow for the standard glue fix application of the particle board flooring. SiteCote coating is still applied to



the wide face and wax seal to the ends. Extra storage care and protection should be taken with LVL that has unsealed surfaces to prevent excessive moisture or water exposure.



In addition it performs exceptionally well in severe conditions such as concrete form beams and joists. SiteCote coating also makes it easy to push in and out of "pigeon holes" at stocking merchant yards.

CONTACT US: PH +61 (0)420 597 366 LPCorp.com/AU

BUILD WITH US.®