

TECHNICAL NOTE: WRB COATINGS APPLIED TO LP® FLAMEBLOCK® FIRE-RATED SHEATHING

Some water-resistive coatings may be used as weather barriers over exterior sheathing during construction. In general, most water-resistive coatings designed for masonry, concrete or gypsum surfaces are compatible with the surface of LP® FlameBlock® Fire-Rated Sheathing. The following coatings have been evaluated and demonstrated to be compatible with LP FlameBlock sheathing by the coating manufacturers. For detailed application procedures, please follow the application instructions for the water-resistive coatings and contact the coatings manufacturers directly to review the application.

| BASF | W.R. MEADOWS | GRACE | DRYVIT | HENRY | DUPONT |
|--------------------------|----------------|---------------------|---------------|------------------|-------------------------|
| Sonoshield® HLM® 5000 | Air-Shield LMP | Perm-A-Barrier® VP | Backstop® NT™ | Air-Bloc® 33MR | Tyvek® Fluid Applied WB |
| Sensershield-R | | Perm-A-Barrier® VPS | | BlueskinVP™ 160* | |
| | | Vycor® enV™ | | | |

*Used with a Henry approved primer

| PROSOCO | DORKEN | DELTA | STO | VAPROSHIELD |
|----------------------------|----------------|-------------------|----------------|------------------|
| R-Guard® Spray Wrap MVP | Delta®-Vent SA | Delta®-Vent SA | Sto Gold Coat® | WrapShield SA® |
| Cat-5 | | Delta®-Stratus SA | | RevealShield SA® |
| R-Guard® VB | | Delta®-Fassade SA | | VaproLiquiFlash |
| Joint and Seam Filler | | | | |
| FastFlash | | | | |



For more information, please visit LPCorp.com/FlameBlock or call 1-888-820-0325.

⚠ CAL PROP. 65 WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood.

© 2019 Louisiana-Pacific Corporation. All rights reserved. Sonoshield and HLM are registered trademarks of the BASF Group. PROSOCO and PROSOCO R-Guard are registered trademarks of Boyer Industries Corporation. Backstop and NT are trademarks of Dryvit Systems, Inc. Tyvek is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates. Perm-A-Barrier, Vycor, and enV are trademarks of GCP Applied Technologies Inc. Air-Bloc and BlueskinVPTM are trademarks of the Henry Company. Delta is a registered trademark of Dörken Systems Inc. RevealShield SA and WrapShield SA are registered trademarks of VaproShield LLC. All other trademarks are owned by Louisiana-Pacific Corporation. Specifications subject to change without notice. LPFB0151 8/19