

Can you apply water-resistive coatings over LP® FlameBlock® Fire-Rated OSB Sheathing?

Some water-resistive coatings may be used as weather barriers over exterior sheathing during construction. In general, most water-resistive coatings designed for masonry, concrete or gypsum surfaces are compatible with the surface of LP® FlameBlock® Fire-Rated OSB Sheathing. The following coatings have been evaluated and demonstrated to be compatible with LP FlameBlock sheathing by the coating manufacturers. For detailed application procedures, please follow the application instructions for the water-resistive coatings and contact the coatings manufacturers directly to review the application.

BASF	W.R. MEADOWS
Sonoshield® HLM® 5000 Sensershield-R	Air-Shield LMP
GRACE	DRYVIT
Perm-A-Barrier® VP Perm-A-Barrier® VPS Vycor® enV™	Backstop® NT™
HENRY	DUPONT
Air-Bloc® 33MR BlueskinVP™ 160* <i>*Used with a Henry approved primer</i>	Tyvek® Fluid Applied WB
PROSOCO	DORKEN
R-Guard® Spray Wrap MVP Cat-5 R-Guard® VB Joint and Seam Filler FastFlash	Delta®-Vent SA

For more information about LP FlameBlock Fire-Rated OSB Sheathing, including our Technical Guide, call 1-888-820-0325, email customer.support@lpcorp.com or visit LPCorp.com/FlameBlock